

IFP FireChek

Foam /Water Fire Extinguisher

Features

- Simple operation and maintenance
- Rechargeable
- Manufactured of durable high quality materials
- Controlled discharge.
- Meets requirements of Indian Standard IS 15683:2018 and ISO 7165:1999
- Easy operation and minimal maintenance
- Operating temperature range is (-)30°C to (+)60°C
- High quality AFFF (BIS Marked and UL Listed) foam for high performance



Approvals

BIS marked as per IS 15683:2018

Specifications

Model	F6-CM	F9-CM	W6-CM	W9-CM
Part Number	304010	304020	305010	305020
Capacity	6L	9L	6L	9L
Type	Foam	Foam	Water	Water
MOC	Mild Steel/SS	Mild Steel/SS	Mild Steel/SS	Mild Steel/SS
Agent	AFFF	AFFF	Water	Water
Discharge time	35 sec	50 sec	35 sec	50 sec
Operating Temperature	(-)30°C to (+)60°C	(-)30°C to (+)60°C	(-)30°C to (+)60°C	(-)30°C to (+)60°C
Throw	3m	4m	3m	3.5m
Fire Rating	3A, 89B	4A, 233B	2A	4A

Ordering Information

Part Number	Description	Weight (kg)
304010	Mechanical Foam, Cartridge Pressure, 6kg	10.4
304020	Mechanical Foam, Cartridge Pressure, 9kg	14.0
305010	Water, Cartridge Pressure, 6kg	10.4
305020	Water, Cartridge Pressure, 9kg	14.0

DATASHEET : EXT004
REVISION : 02/2023

Contacts in Emergency : +919903914042

Integrated Fire Protection Pvt. Ltd.

60A, Pandit Madan Mohan Malabha Sarani, Kolkata - 700 020 INDIA
Phone : (91) (33) 2454-1061, 2475-5634, Fax : (91) (33) 2476-1107

E-mail : info@integratedfire.net
www.integratedfire.net