

Features

- Simple operation and maintenance
- Rechargeable
- Manufactured of durable high quality materials
- Contains carbon dioxide, gaseous agent.
- Useful for B and C classes of fires
- IS marked as per IS 15683:2018
- Meets requirements of Indian Standard ISO 7165:1999.
- Easy operation and minimal maintenance
- Operating temperature range is –30°C to 55 °C (–22°F to 131°F)



Application

Warehousing, Chemical manufacturing plant, auto repair shops, paint process areas, Rail yards, Construction sites, Apartment buildings, Parking garages, Airport, Material handling vehicles and many more

Approvals

BIS marked as per IS 15683:2018

Specifications

Model	C2-SM	C3-SM	C4-SM
Capacity	2 Kg	3 Kg	4.5 Kg
MOC	Steel	Steel	Steel
Height (Approx)	580 mm	545 mm	700 mm
Diameter (Approx)	108 mm	140 mm	140 mm
Discharge time	12 sec	14 sec	14 sec
Test Pressure	250 bar	250 bar	250 bar
Operating Temperature	–30°C to 55°C	–30°C to 55°C	–30°C to 55°C
Fire Rating	21B	34B	55B

Ordering Information

Part Number	Description	Weight (kg)
306010	Carbon dioxide, 2 kg	8.2
306020	Carbon dioxide, 3 kg	10.0
306030	Carbon dioxide, 4.5 kg	16.0

DATASHEET : EXT006
REVISION : 02/2021

Contacts in Emergency : +919903914042

Integrated Fire Protection Pvt. Ltd.

60A, Pandit Madan Mohan Malabha Sarani, Kolkata - 700 020 INDIA

Phone : (91) (33) 2454-1061, 2475-5634, Fax : (91) (33) 2476-1107

E-mail : info@integratedfire.net

www.integratedfire.net