

Low-expansion Foam Liquid Concentrate IFP-FP-3C6

File Number: EX5308

COMPANY

INTEGRATED FIRE PROTECTION PVT LTD
60A
PANDIT MADAN MOHAN MALABYA SARANI
CHAKRABERIA ROAD NORTH
KOLKATA, West Bengal 700020 India

LOW-EXPANSION FOAM LIQUID CONCENTRATE INFO

IFP-FP-3C6
Fluoroprotein

FOAM CONCENTRATES FOR USE WITH THE FOLLOWING EQUIPMENT

Minimum Storage and Use Temperature

+35 F (1.7 C)

GENERAL

Hydrocarbon Fuels, percent

3

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Manufacturer and Model	Use Concentration, percent	Size, in.	Orifice Diameter/Setting	Inlet Pressure, psig	Length and Diameter of hose	Discharge Device Manufacturer and Model
Integrated Fire Protection, Model IFP-II-400(V)	3	2-1/2	set at 3	166-220	15 m of 63.5 mm	Integrated Fire Protection, Model IFP-LX-400

NOZZLES

Manufacturer and Model	Size, in.	Inlet Pressure, psig
IFP-LX-400	2-1/2	57-71

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."